



PAN GREASING

PAN GREASING

PAN GREASING SYSTEM WITHOUT ATOMIZED AIR

Danmatic's Oil Spray System is a highly efficient system for pan greasing, to secure the products being released smoothly after baking.

Spraying is performed without atomized air by PulsaJet® Automatic Spray Nozzles, which offers adjustable high speed pulsing up to 5.000 cycles per minute.

To ensure a clean and healthy environment the liquid is supplied from an integrated pressurised double vessel system directly to the spray guns.

Moreover the spray nozzles are mounted in a stainless steel cabinet, and even the conveyor is designed as a tunnel directing the airflow into the oil mist collectors.

The Oil Spray System is equipped with "Filtermist" to avoid pollution in the surrounding area. Excess oil is led to the collecting tray beneath the conveyor.

BENEFITS

- Clean environment around the machine
- Pressurised liquid to spray nozzles, no atomized air
- "Filtermist" unit close to the spray nozzles

OPTIONS

- "Filtermist" unit in painted or stainless steel execution
- Top cover for infeed conveyor
- Adjustable side guides for straps
- "Filtermist" unit at the outfeed of the tunnel conveyor

TECHNICAL DATA

- Air pressure required, minimum 6 bar
- Double vessel system with level control
- Belt speed according to customer request
- Width dependent on the width of the straps
- Standard length 4.000 mm dependent on the length of the straps, though minimum 3.000 mm
- Manufactured in stainless steel and food approved materials
- Touch panel with 7" colour screen
- Electrical control in separate cabinet on top of the unit

