

[®] danmatic



RETRACTION UNIT

Compact and Industrial Versions

VIBORG Lundvej 16 - DK 8800 Viborg - Denmark - Phone +45 87 25 98 00
KVISTGÅRD Bøgeskovvej 6 - DK 3490 Kvistgård - Denmark - Phone +45 70 20 50 25

RETRACTION UNIT

RETRACTION UNIT

Danmatic's Retracting Unit is designed for precise and gentle deposition of dough piece products onto eg. straps or a conveyor.

Danmatic has for years manufactured two of the strongest Retraction Units in the market.

- A Compact version that fits the retraction length of maximal 2.000 mm and up to 900 mm conveyor width
- An Industrial version with retraction length up to 4.000 mm and 1500 mm conveyor width

Both models are recognized by their compact design, short buildin measurements and by high quality stainless steel materials.

Both models are delivered with their own PLC-control system as well as an adjustable conveyor belt speed control.

Both models have a tiltable nose as well as knife edge of 16 mm to obtain the best possible precision at each retraction.

Both models are equipped with a servo motor for a precise individual retraction.

BENEFITS

- Little space is required
- User friendly
- Quick product replacement

OPTIONS

- Automatic belt alignment

TECHNICAL DATA – COMPACT VERSION

- Retraction length reaches 2.000 mm
- Conveyor width reaches 900 mm
- Retraction speed reaches 1,5 m/sec
- Manufactured in stainless steel and food approved materials

TECHNICAL DATA – INDUSTRIAL VERSION

- Retraction length reaches 4.000 mm
- Conveyor width reaches 1.500 mm
- Retraction speed reaches 1,5 m/sec
- Manufactured in stainless steel and food approved materials

